



Zebra ZT610 label printer Direct thermal / Thermal transfer 203 x 203 DPI 356 mm/sec Wired & Wireless Ethernet LAN Wi-Fi Bluetooth

Brand : Zebra

Product code: ZT61042-T01E100Z

Product name : ZT610

4 inch, 203DPI, Serial, USB, Gigabit Ethernet, Bluetooth 5.3, USB Host, Wi-Fi 6 802.11 AX Card: US & Canada, Includes: Tear Bar, US Cord, Color Touch, ZPL

Zebra ZT610. Print technology: Direct thermal / Thermal transfer, Maximum resolution: 203 x 203 DPI, Print speed: 356 mm/sec. Connectivity technology: Wired & Wireless, Ethernet LAN, Wi-Fi, Bluetooth, Bluetooth version: 5.3, USB port. Product colour: Black, Grey

Printing		Performance	
Print technology *	Direct thermal / Thermal transfer	Processor frequency	800 MHz
Maximum resolution *	203 x 203 DPI	Design	
Print speed *	356 mm/sec	Product colour *	Black, Grey
Maximum printing width *	10.4 cm	Built-in display	✓
Vertical printing	✓	Display *	LCD
Rotated printing	✓	Display diagonal	8.89 cm (3.5")
Paper handling		Display resolution	320 x 240 pixels
Ribbon width	11 cm	Colour display	✓
Ribbon length	450 m	Housing material	Metal
Maximum label length	762 m	Power	
Maximum roll diameter	20.3 cm	AC input voltage	90 - 265 V
Media thickness	0.058 - 0.25 mm	AC input frequency	47-63 Hz
Core diameter	7.62 cm	Operational conditions	
Ports & interfaces		Operating relative humidity (H-H)	20 - 85%
Connectivity technology *	Wired & Wireless	Storage relative humidity (H-H)	20 - 85%
Ethernet LAN *	✓	Operating temperature (T-T)	5 - 40 °C
Wi-Fi *	✓	Storage temperature (T-T)	-30 - 60 °C
Wi-Fi standards	Wi-Fi 6 (802.11ax)	Weight & dimensions	
Bluetooth	✓	Width	268.2 mm
Bluetooth version	5.3	Depth	505 mm
USB port *	✓	Height	395.7 mm
RS-232 ports	1	Weight	22.7 kg
Performance		Technical details	
Page description languages	ZPL, ZPL II	Sustainability certificates	ENERGY STAR
Internal memory	1000 MB	Other features	
Flash memory	2000 MB	Navigation key	✓
Built-in barcodes	1D, 2D, AZTECCODE, CODABAR (NW-7), Code 11, Code 128 (A/B/C), Code 39, Code 49, Code 93, Data Matrix, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, MaxiCode, Micro QR Code, MicroPDF417, PDF417, POSTNET, QR Code, TLC39, UPC-A, UPC-E	Plug and Play	✓
Built-in processor	✓		
Number of fonts	16		

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.