



## Zebra GX430t label printer Thermal transfer 300 102 mm/sec Wired

**Brand :** Zebra

**Product code:** GX43-102410-000

**Product name :** GX430t

GX430t, Thermal Transfer, 300DPI, 102mm/s, 4ips, USB, Serial, Ethernet, 8MB RAM, 4MB Flash, 2.1kg

[Zebra GX430t label printer Thermal transfer 300 102 mm/sec Wired:](#)

The best-in-class enhanced GX430t thermal transfer printer offers the widest range of features, 4 inches per second print speed and 300 dpi resolution to meet all your low- to medium-volume printing requirements. The GX430t has a sleek and compact design, boasts the easiest ribbon loading system on the market, and supports a variety of applications and industries.

The GX430t comes standard with EPL and ZPL programming languages and triple connectivity for easy integration into existing systems. For additional flexibility, 10/100 internal Ethernet and Wireless, 802.11 b/g and Bluetooth, options are also available. Well-suited to any industry and with options such as an adjustable media sensor, cutter and peeler, the GX430t desktop printer is a smart investment that's always a perfect fit.



| Printing                  |                                                                                                     | Performance                       |                                                                                                                                  |
|---------------------------|-----------------------------------------------------------------------------------------------------|-----------------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Print technology *        | Thermal transfer                                                                                    | Certification                     | FCC 15, VCCI, C, EN55022 B, EN6100-3-2, EN6100-3-3, EN55024, CCC, CB IEC 60950: 1991 +A1 +A2 + A3 +A4, TUV NRTL, IRAM, NOM, AAMI |
| Maximum resolution *      | 300                                                                                                 |                                   |                                                                                                                                  |
| Print speed *             | 102 mm/sec                                                                                          |                                   |                                                                                                                                  |
| Paper handling            |                                                                                                     |                                   |                                                                                                                                  |
| Ribbon width              | 11 cm                                                                                               | Power                             |                                                                                                                                  |
| Ribbon length             | 74 m                                                                                                | Power requirements                | 100 - 240V, 50/60Hz                                                                                                              |
| Maximum label width       | 10.8 cm                                                                                             | Operational conditions            |                                                                                                                                  |
| Maximum label length      | 0.991 m                                                                                             | Operating relative humidity (H-H) | 10 - 90%                                                                                                                         |
| Maximum roll diameter     | 12.7 cm                                                                                             | Storage relative humidity (H-H)   | 5 - 95%                                                                                                                          |
| Media thickness           | 0.08 - 0.2 mm                                                                                       | Operating temperature (T-T)       | 5 - 41 °C                                                                                                                        |
| Ports & interfaces        |                                                                                                     | Storage temperature (T-T)         | -40 - 60 °C                                                                                                                      |
| Connectivity technology * | Wired                                                                                               | Weight & dimensions               |                                                                                                                                  |
| RS-232 ports              | 1                                                                                                   | Width                             | 194 mm                                                                                                                           |
| RS-232 interface          | ✓                                                                                                   | Depth                             | 254 mm                                                                                                                           |
| Standard interfaces       | Serial, Ethernet                                                                                    | Height                            | 191 mm                                                                                                                           |
| Optional connectivity     | Bluetooth, Parallel, Wireless LAN                                                                   | Weight                            | 2.1 kg                                                                                                                           |
| Performance               |                                                                                                     | Packaging data                    |                                                                                                                                  |
| Internal memory           | 8 MB                                                                                                | Package weight                    | 4.1 kg                                                                                                                           |
| Flash memory              | 4 MB                                                                                                | Packaging content                 |                                                                                                                                  |
| Built-in barcodes         | CODABAR (NW-7), EAN128, EAN13, EAN8, Industrial 2/5, Interleaved 2/5, PDF417, POSTNET, UPC-A, UPC-E | Drivers included                  | ✓                                                                                                                                |
|                           |                                                                                                     | Other features                    |                                                                                                                                  |
|                           |                                                                                                     | Network ready                     | ✓                                                                                                                                |
|                           |                                                                                                     | Emulations                        | EPL, ZPL                                                                                                                         |

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.