



## Zebra ZQ610 Plus label printer Direct thermal 203 x 203 DPI 115 mm/sec Wired & Wireless Wi-Fi Bluetooth

**Brand :** Zebra

**Product code:** ZQ61-AUX2004-00

**Product name :** ZQ610 Plus

Direct thermal, 203 dpi, 256MB RAM, 512MB Flash, 802.11ax, Bluetooth 5.3, USB 2.0  
Zebra ZQ610 Plus. Print technology: Direct thermal, Maximum resolution: 203 x 203 DPI, Print speed: 115 mm/sec. Connectivity technology: Wired & Wireless, Wi-Fi, Bluetooth, Bluetooth version: 5.3, USB port. Product colour: Black



| Printing                      |                            | Performance                        |                                                                                   |
|-------------------------------|----------------------------|------------------------------------|-----------------------------------------------------------------------------------|
| Print technology *            | Direct thermal             | Security algorithms                | 802.1x RADIUS, AES, EAP-FAST, EAP-TLS, EAP-TTLS, LEAP, PEAP, TKIP, WEP, WPA, WPA2 |
| Maximum resolution *          | 203 x 203 DPI              | <b>Design</b>                      | Product colour *<br>Black                                                         |
| Print speed *                 | 115 mm/sec                 |                                    |                                                                                   |
| Maximum printing width *      | 4.8 cm                     |                                    |                                                                                   |
| Maximum print height          | 81.3 cm                    |                                    |                                                                                   |
| Vertical printing             | ✓                          | Built-in display                   | ✓                                                                                 |
| <b>Paper handling</b>         |                            | Display *                          | LCD                                                                               |
| Maximum label width           | 4.8 cm                     | Display resolution                 | 288 x 240 pixels                                                                  |
| Maximum roll diameter         | 5.59 cm                    | Colour display                     | ✓                                                                                 |
| <b>Ports &amp; interfaces</b> |                            | <b>Battery</b>                     |                                                                                   |
| Connectivity technology *     | Wired & Wireless           | Battery technology                 | Lithium-Ion (Li-Ion)                                                              |
| Wi-Fi *                       | ✓                          | Battery capacity                   | 3250 mAh                                                                          |
| Wi-Fi standards               | Wi-Fi 6 (802.11ax)         | <b>System requirements</b>         |                                                                                   |
| Bluetooth                     | ✓                          | Mobile operating systems supported | Android, Windows Mobile, iOS                                                      |
| Bluetooth version             | 5.3                        | <b>Operational conditions</b>      |                                                                                   |
| USB port *                    | ✓                          | Operating relative humidity (H-H)  | 10 - 90%                                                                          |
| USB 2.0 ports quantity        | 1                          | Storage relative humidity (H-H)    | 10 - 90%                                                                          |
| RS-232 ports                  | 1                          | Operating temperature (T-T)        | -20 - 50 °C                                                                       |
| <b>Performance</b>            |                            | Storage temperature (T-T)          | -25 - 65 °C                                                                       |
| Page description languages    | CPCL-native, EPL, ZBI, ZPL | <b>Weight &amp; dimensions</b>     |                                                                                   |
| Internal memory               | 256 MB                     | Width                              | 89 mm                                                                             |
| Flash memory                  | 512 MB                     | Depth                              | 165 mm                                                                            |
|                               |                            | Height                             | 70 mm                                                                             |

| Performance       |                                                                                                                                                                                                               | Weight & dimensions |       |
|-------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|-------|
| Built-in barcodes | 2D, AZTECCODE, CODABAR (NW-7), Code 128 (A/B/C), Code 39, Code 93, Data Matrix, EAN128, EAN13, EAN8, GS1 DataBar, Interleaved 2/5, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC39, UPC-A, UPC-E | Weight              | 600 g |
| Number of fonts   | 25                                                                                                                                                                                                            |                     |       |

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.