



Zebra GK420t label printer Direct thermal / Thermal transfer 203 x 203 DPI 127 mm/sec Wired

Brand : Zebra

Product code: GK42-102510-000

Product name : GK420t

GK420t - 203dpi, 1:1, 4 MB Flash, 8 MB SDRAM, USB 1.1, 2100g, Black

[Zebra GK420t label printer Direct thermal / Thermal transfer 203 x 203 DPI 127 mm/sec Wired:](#)

The Zebra GK420t thermal transfer printer offers the best value in a basic desktop printer, featuring a fast 5 inches per second print speed to meet your low- to medium-volume printing requirements. The GK420t has a sleek and compact design, boasts the easiest ribbon loading system on the market, and supports a variety of applications and industries.

Benefits

- Best value in a desktop printer.
- Enhanced performance and speed.
- Built for ease-of-use and durability.

Standard Features

- Print speed: up to 5" (127 mm) per second.
- Print method: direct thermal/thermal transfer.
- EPL and ZPL programming languages standard.
- OpenACCESS design for easy media loading.
- Quick and easy ribbon loading system.
- Dual-wall reinforced plastic construction.
- 32 bit RISC processor.
- XML-enabled printing.



Printing		Performance	
Print technology *	Direct thermal / Thermal transfer	Flash memory	4 MB
Maximum resolution *	203 x 203 DPI	Built-in barcodes	CODABAR (NW-7), EAN13, EAN8, Industrial 2/5, Interleaved 2/5, UPC-A, UPC-E
Print speed *	127 mm/sec		FCC 15, VCCI, C-Tick, EN55022 B, EN6100-3-2, EN6100-3-3, EN55024, CCCCB IEC 60950: 1991 +A1 +A2 + A3 +A4, TUV NRTL, IRAM, NOM, AAMI
Paper handling			Certification
Ribbon length	74 m		
Maximum roll diameter	12.7 cm		
Media thickness	0.08 - 0.2 mm		
Media thickness (imperial)	0.003 - 0.0075"		
Supported paper width	104 mm		
Supported paper width (imperial)	4.09"		
Maximum media length	99.1 cm		
Maximum media length (imperial)	39"	Design	
		Product colour *	Black
Ports & interfaces		Power	
Connectivity technology *	Wired	Power requirements	100-240V, 50-60Hz
Parallel ports quantity	1	Operational conditions	
RS-232 ports	1	Operating relative humidity (H-H)	10 - 90%
RS-232 interface	✓	Operating temperature (T-T)	40 - 105 °F
USB 1.1 ports quantity	1	Operating temperature (T-T)	5 - 41 °C
Performance		Storage temperature (T-T)	-10 - 140 °F
Internal memory	8 MB	Weight & dimensions	
		Width	194 mm
		Depth	254 mm
		Height	191 mm
		Weight	2.1 kg
		Packaging data	
		Package weight	4.1 kg

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.