



## Zebra DS4608-HD Handheld bar code reader 1D/2D LED Black

**Brand :** Zebra

**Product code:** DS4608-HD7U2600ZCW

**Product name :** DS4608-HD

1D/2D/OCR/OCR, 660 nm LED, 1280x800, 340 mA, IP52, EAS, 165x67x98 mm, Black + CBA-U26-S09EAR Cable

Zebra DS4608-HD. Type: Handheld bar code reader, Scanner type: 1D/2D, Sensor type: LED. Connectivity technology: Wired, Standard interfaces: RS-232, USB. Product colour: Black, International Protection (IP) code: IP52, Certification: 2011/65/EU, EN 50581:2012, EN IEC 63000:2018 UL 60950-1, CAN/CSA-C22.2 No. 60950-1-07. EN.... Power source type: DC, Input voltage: 4.5-5.5 V, Power consumption: 340 mA. Weight: 161.9 g, Width: 67 mm, Depth: 98 mm



| Scanning                                   |                                                                                                                              | Performance                       |                                                                                                                                                                                                                                                                                                                               |
|--------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Type *                                     | Handheld bar code reader                                                                                                     | Certification                     | 2011/65/EU, EN 50581:2012, EN IEC 63000:2018 UL 60950-1, CAN/CSA-C22.2 No. 60950-1-07. EN 60950-1:2006/A2:2013 IEC 60950-1:2005/A2:2013 IEC 62368-1 (ed.2); EN 62368-1:2014 IEC 62471:2006 (Ed.1.0); EN 62471:2008 FCC: 47 CFR 15, B, B ICES-003 6, B, EN 55032, B, EN 55024, EN 55035, EN 60601-1-2:2015, IEC 60601-1-2:2014 |
| Scanner type *                             | 1D/2D                                                                                                                        |                                   |                                                                                                                                                                                                                                                                                                                               |
| Sensor type *                              | LED                                                                                                                          |                                   |                                                                                                                                                                                                                                                                                                                               |
| Linear (1D) barcodes supported *           | Codabar, Code 11, Code 128, Code 32, Code 39, Code 93, GS1 DataBar, Industrial 2 of 5, MSI, Plessey                          |                                   |                                                                                                                                                                                                                                                                                                                               |
| 2D (matrix & stacked) barcodes supported * | Aztec Code, Composite Codes, Data Matrix, Dot Code A, Han Xin, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC-39 |                                   |                                                                                                                                                                                                                                                                                                                               |
| Optical sensor resolution (W x H)          | 1280 x 800 pixels                                                                                                            | Power                             |                                                                                                                                                                                                                                                                                                                               |
| Wavelength                                 | 660 nm                                                                                                                       | Power source type *               | DC                                                                                                                                                                                                                                                                                                                            |
| Pitch reading angle                        | -60 - 60°                                                                                                                    | Input voltage                     | 4.5-5.5 V                                                                                                                                                                                                                                                                                                                     |
| Ports & interfaces                         |                                                                                                                              | Power consumption                 | 340 mA                                                                                                                                                                                                                                                                                                                        |
| Connectivity technology *                  | Wired                                                                                                                        | Weight & dimensions               |                                                                                                                                                                                                                                                                                                                               |
| Standard interfaces *                      | RS-232, USB                                                                                                                  | Width                             | 67 mm                                                                                                                                                                                                                                                                                                                         |
| Performance                                |                                                                                                                              | Depth                             | 98 mm                                                                                                                                                                                                                                                                                                                         |
| International Protection (IP) code         | IP52                                                                                                                         | Height                            | 165 mm                                                                                                                                                                                                                                                                                                                        |
| LED indicators                             | ✓                                                                                                                            | Weight *                          | 161.9 g                                                                                                                                                                                                                                                                                                                       |
| Product colour *                           | Black                                                                                                                        | Operational conditions            |                                                                                                                                                                                                                                                                                                                               |
|                                            |                                                                                                                              | Operating temperature (T-T)       | 0 - 50 °C                                                                                                                                                                                                                                                                                                                     |
|                                            |                                                                                                                              | Storage temperature (T-T)         | -40 - 70 °C                                                                                                                                                                                                                                                                                                                   |
|                                            |                                                                                                                              | Operating relative humidity (H-H) | 5 - 95%                                                                                                                                                                                                                                                                                                                       |

| Operational conditions          |          |
|---------------------------------|----------|
| Storage relative humidity (H-H) | 5 - 95%  |
| Logistics data                  |          |
| Harmonized System (HS) code     | 84716070 |

## Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.