



Zebra LS2208 Handheld bar code reader 1D Laser Black, White

Brand : Zebra

Product code: LS2208-1AZU0100ZNA

Product name : LS2208



1D, 100 Reads/s, 86080 lx, 650 nm, IP30, 4.5-5.5 VDC

Zebra LS2208. Type: Handheld bar code reader, Scanner type: 1D, Sensor type: Laser. Connectivity technology: Wired, Standard interfaces: RS-232, RS-485, Keyboard wedge, USB. Product colour: Black, White, International Protection (IP) code: IP30, Protection features: Drop resistant, Scratch resistant. Power source type: DC, Input voltage: 4.5 - 5.5 V, Power consumption: 175 mA. Weight: 150 g, Width: 64 mm, Depth: 85 mm

Scanning		Performance				
Type *	Handheld bar code reader	Certification	EN 60950-1: 2006 + A11: 2009 + A1: 2010 + A12: 2011 + AC 2011; IEC 60950-1: 2005 + A1: 2009; UL 60950-1, second edition; CAN/CSA-C22.2 No. 60950-1-07 FCC 47 CFR Part 15, Subpart B, Class B; ICES-003 Issue 4, Class B; Compliant with EMC Directive 2004/108/EC CDRH Class II; IEC Class 2			
Scanner type *	1D					
Sensor type *	Laser					
Linear (1D) barcodes supported *	Codabar, Code 11, Code 128, Code 39 (ASCII), Code 93, GS1 DataBar, Pharmacode, Plessey, Standard 2 of 5					
Scanner resolution	3 mm					
Working distance	63.5 cm					
Read rate (max)	100 reads/s					
Light levels (direct sunlight)	0 - 86080 lx					
Wavelength	650 nm					
Tilt reading angle	-10 - 10°	Power	Power source type *	DC		
Pitch reading angle	-65 - 65°				Input voltage	4.5 - 5.5 V
Yaw reading angle	-60 - 60°					
Ports & interfaces		Weight & dimensions				
Connectivity technology *	Wired	Width	64 mm			
Standard interfaces *	RS-232, RS-485, Keyboard wedge, USB	Depth	85 mm			
		Height	152 mm			
		Weight *	150 g			
Performance		Packaging data				
International Protection (IP) code	IP30	Cables included	USB			
Protection features	Drop resistant, Scratch resistant	Stand included	✓			
LED indicators	✓	Operational conditions				
Product colour *	Black, White	Operating temperature (T-T)	0 - 50 °C			
		Storage temperature (T-T)	-40 - 70 °C			
		Operating relative humidity (H-H)	5 - 95%			
		Drop resistance	0.5 m			
		Technical details				
		Compliance certificates	Federal Communications Commission (FCC), RoHS			

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.